

NEW! Palmer Pelican Case Portable Chart Recorder for Tough Outdoor Environments



Chart stays dry regardless of the weather!

NEW! Palmer Pelican® Case Recorder - our top quality 8" chart recorder now comes housed in a rugged Pelican case. Double-throw latches and water-tight O-ring seal assures protection even in harsh environments. Lightweight and easy to carry, the new Palmer Pelican Case Recorder offers the convenience and protection you need in a recorder.

Palmer Chart Recorders come complete with either PC-11 (battery operated) chart drive as standard, or optional spring wound. Temperature and Pressure can be combined inside the same recorder with up to three (3) systems. Palmer Recorders are made in the USA!

Case Features

- Watertight, Crushproof, and Dust proof.
- Plexiglass Window (Std) or optional Solid Door.
- Double Throw Latches and Watertight O-ring Seals.
- Open cell core with solid wall design - strong and light weight.
- Automatic Pressure Equalization Valve releases built-up pressure and prevents moisture intrusion.
- Comfortable rubber over-molded handle.
- Stainless Steel padlock protectors provide extra strength when locking against tamper resistance.
- Heavy Duty Deflector Ribs to protect against shock and impact.
- NO SLIP rubberized adjustable feet, keep recorder balanced.

Recorder Features

- All internal components are corrosion resistant.
- Pen assembly is designed to transmit the movement of the sensors into a smooth, gliding arc across the chart. This prevents burrowing, resulting in longer pen life and better accuracy and readability.
- Micro adjustment feature simplifies calibration.
- Wire linkage.

Recorder Specifications

Pressure Ranges: inH₂O Ranges from 0 to 100, Hg Ranges from 0 to 50, kPa Ranges from 0 to 5,000, oz/in² Ranges from 0 to 50, PSI Ranges from 0 to 30,000.

Accuracy: $\pm 1/2$ chart graduation.

Pressure Elements: High pressure helical wound bourdon coil for ranges over 30 PSIG, Low pressure diaphragm for ranges under 30 PSIG.

Temperature Ranges: from 0°F to 1000°F, and 0° to 600°C.

Accuracy: ± 1 chart graduation.

Temperature Elements: Mercury filled systems, the most accurate in the world, conform to ASME, and 5A and 5B, and offer rapid response to temperature changes.

Pens: Fine point, felt tip pens in Red, Green and Blue. Other colors available.

Chart Drives: PC-11 Battery Operated Chart Drive (Std) - 11 speeds allows selectable recording intervals from 60 min., 96 min., 12 hr., 1 day, 2 day, 7 day, 8 day, 14 day, 16 day, 31 day or 32 day recording intervals. Hermetically sealed, Intrinsically safe. Spring Wound: 24 hours and 7 days, or optional 15 minute and 1 hour.

Chart: 1 Box of Charts included.

Case Dimensions (Exterior, without Handle and Feet):
18.5" x 14.06" x 6.93" (47 x 35.7 x 17.6 cm)

Case Weight (Empty):
6.39 lbs (2.9 kg)




Specifications subject to change without notice.

NEW! Palmer Pelican Case Portable Chart Recorder


Temperature Elements

Palmer's temperature elements must pass stringent quality control. All mercury filled systems conform to ASME and other designations such as 5A or 5B. Each system is pressurized after filling so it will have overrange capabilities above and below its specified range. Rapid response to changes in temperature make it extremely accurate and reliable. The system is completely welded to prevent deterioration. Points most susceptible to physical damage are reinforced with added flexible armor.


- Carefully heat treated coil provides superior spring action
- Durable, low maintenance design: thermal system and other parts easily replaced by field technician
- 300 Series stainless steel bulb, interconnection capillary, and armor available on certain designs
- Standard case compensated system for uncompensated capillary lengths not exceeding 25'.
- Standard ranges: from 0°F to 1000°F, and 0° to 600°C.




Bulb 45-5
Plain bulb of stainless steel




Bulb 45-11
Bendable stiff armor between plain bulb and flexible armor




Bulb 45-12
Bendable stiff armor between plain bulb and swivel nut




Bulb 45-13
Bulb for well or union connection



Bulb 45-14 standard
Bulb construction permits instrument to be used in wells of varied lengths



Bulb 45-29
Plain air temperature bulb with rings for suspending in air stream



Bulb 45-30
Air temperature bulb for union connection

Note: Air type bulbs have standard outside diameter of 5/16" and 3/8".


Specifications subject to change without notice.



Pressure Elements

Each Palmer pressure element is individually designed and calibrated for one service pressure range to ensure better than specified accuracy. The all-welded system prevents deterioration.

- 316 S.S. helical type coil with S.S. fittings and tubing, all welded construction offers over-range protection for ranges over 30 PSIG. Ranges up to 10,000 PSI have a 1/4" NPT female connection. Ranges above 10,000 PSI have a 9/16"-18 UNF Female Autoclave Engineers Fitting with a 60 Degree conical seat. (Optional on 10,000 PSI).
- Beryllium copper diaphragm silver brazed to copper tubing and brass fittings for ranges under 30 PSIG (with 1/4" NPT female connection).
- Angular deflection of the pen arm of 22-1/2 degrees for 8" and 36 degrees for 12".
- Standard ranges: inH₂O Ranges from 0 to 100, Hg Ranges from 0 to 50, kPa Ranges from 0 to 5,000, oz/in² Ranges from 0 to 50, PSI Ranges from 0 to 30,000.



Low pressure
diaphragm for
ranges under
30 PSIG



High pressure helical
wound bourdon coil for
ranges over 30 PSIG

**Palmer recorders are
hand-crafted in the USA to
last longer than any other
product on the market!**



PALMER Wahl
INSTRUMENTATION GROUP
Continued Innovation Since 1836
ISO 9001:2008 CERTIFIED